

# PARKETOLIT

# E61

## SUPERIOR QUALITY & EASY-TO-USE & USER FRIENDLY

### Using for gluing:

- **All types of parquet:** multy-layer parquet, solid parquet elements, mosaic parquet, solid lamparquet, solid boards up to 210 mm in width, solid vertical finger parquet
- **On any kind of subfloor:** on porous (cement, wooden, anhydrite), on unporous (ceramics, marble), on heating installations and on the wet cement subfloors with moisture content up to 4CM% **even without using primer.**

### Superior quality:

- One component STP (silane terminated polyurethane) adhesive
- **Soft adhesive** according to **EN 14293:2006** standard and **hard-elastic adhesive** according to **ISO 17178:2013** requirements for adhesives for gluing parquet
- With licence: **EMICODE EC1 PLUS R – very low emission,**
- **Allows natural adaptation** of wooden floors to ambient conditions
- **Improves sound isolation** of floor




### User friendly characteristics:

- Odour, water and solvent free
- Ready-to-use
- Packing into aluminium bags enabling maximal utilization of the glue
- Easy spreading with notched trowel
- Keeps the form of applying
- Long open time: approx. 60 minutes at 20°C
- Easy to clean of residues from surface treated parquet
- Easy to remove from tools and hands
- Additional operations are possible after 24 hours

### Packing:

- Packed into aluminium foil bags to provide long shelf life and using without any waste
- Plastic vessel of 14 kg (2x7kg aluminium bags), 1 pallet = 44 vessels, total 616 kg.

For more information, please call **++386 573 12 315** or mail to [prodaja@mitol.si](mailto:prodaja@mitol.si).



# WE'RE ALWAYS IN BETWEEN



# CHOOSE THE RIGHT ADHESIVE

	PARKETOLIT 1513	PARKETOLIT 1514	PARKETOLIT 1549	PARKETOLIT 1550	PARKETOLIT 1551	PARKETOLIT 1554	PARKETOLIT 1555	PARKETOLIT E60	PARKETOLIT E61	PARKETOLIT E65	PARKETOLIT E66	PARKETOLIT D3	MEKOL 1560	MEKOL 1570	MEKOL 1580	MITOPUR 1530
<b>SOLID PARQUET ELEMENTS</b>																
• on concrete or on leveller	■	■	●	●	●	●	●	●	●	●	●					
• on wooden floors		■	●	●	●	●	●	●	●	●	●					
• on nonporous surfaces			●	●	●	●	●	●	●	●	●					
• on heated floors			●	●	●	■	■	●	●	●	●					
• on concrete with increasing moisture			■	■	■	■	■	●	●	■	■					
• unstable wood (beech, ash...)			■	■	■	■	●	●	●	●	●					
<b>MOSAIC PARQUET</b>																
• on concrete or on leveller	●	●	●	●	●	●	●	●	●	●	●					
• on wooden floors		●	●	●	●	●	●	●	●	●	●					
• on nonporous surfaces			●	●	●	●	●	●	●	●	●					
• on heated floors	●	■	●	●	●	■	■	●	●	●	●					
• on concrete with increasing moisture			■	■	■	■	■	●	●	■	■					
• unstable wood (beech, ash...)			●	●	●	●	●	●	●	●	●					
<b>SOLID LAMPARQUET</b>			●	●	●	●	●	●	●	■	■					
<b>SOLID BOARDS</b>			●	●	●	●	●	■	■	■	■					
<b>MULTY-LAYER PARQUET</b>			■	■	■	●	●	●	●	●	●	●				
<b>SOLID VERTICAL FINGER PARQUET</b>			●	●	●	●	●	●	●	●	●					
<b>LAMINATED FLOORS</b>								■	■	■	■	●				
<b>PVC</b>													●	●	●	■
<b>TEXTILE COVERINGS</b>													●	●		
<b>CORK (natural, plastic)</b>														●		
<b>RUBBER</b>			■	■	■			■	■	■	■				●	●
<b>LINOLEUM</b>															●	
<b>CERAMIC TILES</b>			■	■	■	■	■	■	■	■	■					■
<b>ARTIFICIAL GRASS</b>			■	■	■	■	■									●
<b>WOODEN STEPS</b>			■	■	■	■	■	■	■	■	■					■

● basic use

■ possible use



MITOL, tovarna lepil, d.o.o., Sežana, Partizanska c. 78, 6210 Sežana, Slovenija  
T: +386 5 73 12 300, F: +386 5 73 12 390, E: [mitol@mitol.si](mailto:mitol@mitol.si), I: [www.mitol.si](http://www.mitol.si)