

# MEKOL MONT

## assembling adhesive

<b>DESCRIPTION</b>	MEKOL MONT is a water dispersed solvent free assembling adhesive. Benefits of adhesive: <ul style="list-style-type: none"> <li>- odour &amp; solvent free</li> <li>- excellent initial grip</li> <li>- fast setting: more than 50% of final strength in less than 10 minutes</li> <li>- high final strength: 120 kg/cm<sup>2</sup></li> <li>- easy cleaning with water the rests of adhesive</li> </ul>									
<b>FIELDS OF APPLICATION</b>	Assembling adhesive for quick fixing of battens, ceramic tiles, insulation materials, Styropor plates, cork, textile coverings etc. on rough-cast, concrete, gypsum, wood or on other porous surfaces. Useless for polyethylene, polypropylene and Teflon. For indoor use.									
<b>CHARACTERISTICS</b>	Colour: Viscosity at 20°C (Brookfield) Total solids (ISO 3251) Yield:	white  paste min. 65% 300 mL/9m								
<b>DANGEROUS GOODS CLASSIFICATION</b>	The product is not classified as dangerous.									
<b>APPLICATION</b>	The surfaces must be dry, clean and free of oil, grease, remains of paints and dust. Apply the adhesive by manual gun into one of the surfaces in point or line form in a 0.5 to 1 cm thick layer. Connect both surfaces, press and fix them. When use the adhesive for gluing Styropor plates, fixing is not necessary although for gluing on ceiling. Clean the adhesive stains with a wet rag. The adhesive bonds in 15-60 minutes, depend on the surfaces, temperatures and humidity. Avoid gluing at the temperatures less than + 10°C.									
	<b>The most convenient working conditions:</b> <table border="0" style="width: 100%;"> <tr> <td>Temperature of room and all materials involved</td> <td>18-25°C</td> </tr> <tr> <td>Relative air humidity</td> <td>65-75%</td> </tr> <tr> <td>Moisture of cementitious surface</td> <td>max. 3%</td> </tr> <tr> <td>Moisture of wood</td> <td>max. 12%</td> </tr> </table>		Temperature of room and all materials involved	18-25°C	Relative air humidity	65-75%	Moisture of cementitious surface	max. 3%	Moisture of wood	max. 12%
Temperature of room and all materials involved	18-25°C									
Relative air humidity	65-75%									
Moisture of cementitious surface	max. 3%									
Moisture of wood	max. 12%									
<b>PACKING</b>	Available in 300 ml cartridges.									
<b>STORAGE</b>	Keep the product sealed in its original container at a temperature between +5°C and +25°C. <b>PROTECT FROM FREEZE!</b> The shelf life of the correctly stored product is minimum 18 months.									

The information provided herein, especially recommendations for the usage and application of our products, is based on our knowledge, results of laboratory tests and practical experience gained to date.

We guarantee a constant quality of our products under our technical specifications. Technical advice of our application department is available without obligation. This does not release the buyer from testing our products in his own responsibility with respect to their suitability for intended application and application process. Such an evaluation should be repeated if materials are changed in any way or bought from a different source.

We do not accept any liability with regard to above information or with regard to any verbal recommendation since different materials used in conjunction with our products as well as varying working conditions are beyond our control.