

MITOPUR R2

POLYURETHANE CONTACT ADHESIVE

NEW! Improved quality and simplify application of adhesive.

For gluing and repairing of hard or soft PVC, leather, textile, rubber, polyurethane foam and other materials, which would be exposed to water, high mechanical, temperature or outside climate conditions.

NEW CHARACTERISTICS OF MITOPUR R2:

Using of one component adhesive, gluing joint is:

- **Transparent,**
- **Strong,**
- **Flexible,**
- **Water resistant and**
- **Temperature resistant**
from -20°C to +90°C.



EASY TO USE ADHESIVE:

- **Ready to use** one component adhesive.
- **Metal notched trowel** is added to packaging, using for easy opening of metal tin and for equally spreading of adhesive.



Easy opening of metal tin



Equally spreading of adhesive

APPLICATION

Surfaces to be bonded should be dry, clean, oil and dust free. Adhesive should be applied on both sides in equal thin layer in quantity 100 - 200 g/m² depend on roughness and porosity of gluing materials. Very porous materials should be coated twice within 5 to 10 minutes.

Spread the adhesive on both materials, dry it for 3 to 5 minutes that solvents can partly evaporate. Stick the materials together and press them manually.

WE'RE ALWAYS IN BETWEEN



FIELDS OF APPLICATION

FOR GLUING AND REPAIRING IN INDUSTRY, CRAFT AND DOMESTIC APPLICATIONS

- Products of hard and soft PVC:



- Footwear and leather products:



- Textile and plasticized materials:



- Products of soft and hard polyurethane (PU) foam:



- Coverings, gaskets, transport lines from various types of rubber:



For more information, please call **++386 573 12 326** or mail to **prodaja@mitol.si**.



MITOL, tovarna lepil, d.o.o., Sežana, Partizanska c. 78, 6210 Sežana, Slovenija
T: ++386 5 73 12 300, F: ++386 5 73 12 390, E: mitol@mitol.si, I: www.mitol.si