

# PARKETOLIT

# 1554

## 2c EPOXY-PU ADHESIVE FOR PARQUET

### For gluing:

- **All types of parquet:** multy-layer parquet, solid parquet elements, mosaic parquet, solid lamparquet, solid boards, solid vertical finger parquet
- **On any kind of subfloor:** on porous (cement, wooden, anhydrite) and on unporous (ceramics, marble) ...

### With using primer Parketolit PR50 suitable also:

- For **wet cement subfloors** with residual moisture content from 2 to 4 CM%.
- **On underfloor heating installations.**

### Characteristics:

- Water and highly volatile solvents free,
- Easily spread with notched trowel,
- Keeps the form of applying,
- Long pot life of the mixture A+B: (45-60 minutes, 15kg at 20°C),
- Long open time: (90-120 minutes at 20°C).

### Benefits from using adhesive:

- It is highly recommended for laying prefinished parquet because of easy cleaning of adhesive residues from parquet surface. Allows also easy removing from tools and hands.
- Sanding and lacquering are already possible one day after laying parquet.
- Lasting quality joint.

### Spreading quantity:

- with notched trowel B3: 800-900 g/m<sup>2</sup>
- with notched trowel B11: 1000-1500 g/m<sup>2</sup>

### Packing:

- plastic vessel of 15kg (14kg A+ 1kg B),  
1 pallet = 44 vessels, total 660kg.

For more information, please call **++386 573 12 326** or mail to [prodaja@mitol.si](mailto:prodaja@mitol.si).



Universal adhesive for all types of parquet on any kind of subfloor.



Easy-to-apply, easy-to-clean, long open time.



Sanding and lacquering are possible already next day after laying parquet.



MITOL, tovarna lepil, d.o.o., Sežana, Partizanska c. 78, 6210 Sežana, Slovenija  
T: +386 5 73 12 300, F: +386 5 73 12 390, E: [mitol@mitol.si](mailto:mitol@mitol.si), I: [www.mitol.si](http://www.mitol.si)

# CHOOSE THE RIGHT ADHESIVE

	PARKETOLIT 1513	PARKETOLIT 1514	PARKETOLIT 1549	PARKETOLIT 1550	PARKETOLIT 1551	PARKETOLIT 1554	PARKETOLIT 1555	PARKETOLIT E60	PARKETOLIT E61	PARKETOLIT E65	PARKETOLIT E66	PARKETOLIT D3	MEKOL 1560	MEKOL 1570	MEKOL 1580	MITOPUR 1530
<b>SOLID PARQUET ELEMENTS</b>																
• on concrete or on leveller	■	■	●	●	●	●	●	●	●	●	●					
• on wooden floors		■	●	●	●	●	●	●	●	●	●					
• on nonporous surfaces			●	●	●	●	●	●	●	●	●					
• on heated floors			●	●	●	■	■	●	●	●	●					
• on concrete with increasing moisture			■	■	■	■	■	●	●	■	■					
• unstable wood (beech, ash...)			■	■	■	■	●	●	●	●	●					
<b>MOSAIC PARQUET</b>																
• on concrete or on leveller	●	●	●	●	●	●	●	●	●	●	●					
• on wooden floors		●	●	●	●	●	●	●	●	●	●					
• on nonporous surfaces			●	●	●	●	●	●	●	●	●					
• on heated floors	●	■	●	●	●	■	■	●	●	●	●					
• on concrete with increasing moisture			■	■	■	■	■	●	●	■	■					
• unstable wood (beech, ash...)			●	●	●	●	●	●	●	●	●					
<b>SOLID LAMPARQUET</b>			●	●	●	●	●	●	●	■	■					
<b>SOLID BOARDS</b>			●	●	●	●	●	■	■	■	■					
<b>MULTY-LAYER PARQUET</b>			■	■	■	●	●	●	●	●	●	●				
<b>SOLID VERTICAL FINGER PARQUET</b>			●	●	●	●	●	●	●	●	●					
<b>LAMINATED FLOORS</b>								■	■	■	■	●				
<b>PVC</b>													●	●	●	■
<b>TEXTILE COVERINGS</b>													●	●		
<b>CORK (natural, plastic)</b>														●		
<b>RUBBER</b>			■	■	■			■	■	■	■				●	●
<b>LINOLEUM</b>															●	
<b>CERAMIC TILES</b>			■	■	■	■	■	■	■	■	■					■
<b>ARTIFICIAL GRASS</b>			■	■	■	■	■									●
<b>WOODEN STEPS</b>			■	■	■	■	■	■	■	■	■					■

● basic use

■ possible use

