

# PARKETOLIT

# 1551

## SUPERIOR QUALITY & UNIVERSAL & USER FRIENDLY

### Using for gluing:

- **All types of parquet:** solid parquet elements, mosaic parquet, solid lamparquet, solid boards, solid vertical finger parquet, multy-layer parquet
- **On any kind of subfloor:** on porous (cement, wooden, anhydrite) and on unporous (ceramics, marble), etc.
- Suitable also for **wet cement subfloors** with residual moisture content from 2 to 4 CM% with using primer Parketolit PR51 or Parketolit PR50
- On underfloor **heating installations**
- **Indoor and outdoor**

### Superior quality:

- Two component polyurethane adhesive
- **Hard adhesive** according to **EN 141293:2006** and **ISO 17178:2013** requirements for gluing parquet
- With licence:  
**EMICODE EC1 PLUS – very low emission**
- **Resistant to outdoor conditions**



### User friendly characteristics:

- Odour, water and solvent free
- Easy spreading with notched trowel
- Keeps the form of applying,
- Long pot life of the mixture A+B: (40-50 minutes, 14kg at 20°C),
- Long open time: 90-120 minutes at 20°C,
- Curing without spread quantity limits,
- Full traffic and additional operations are possible after 24 hours

### Spreading quantity:

- with notched trowel B3: 800-900 g/m<sup>2</sup>
- with notched trowel B11: 900-1500 g/m<sup>2</sup>

### Packing:

- All-in-one set for easy transport and use
- Plastic vessel of 14 kg (12kg A+ 2x1kg B), 1 pallet = 44 vessels, total 616 kg.

For more information, please call **++386 573 12 315** or mail to **prodaja@mitol.si**.

## WE'RE ALWAYS IN BETWEEN



# CHOOSE THE RIGHT ADHESIVE

	PARKETOLIT 1513	PARKETOLIT 1514	PARKETOLIT 1549	PARKETOLIT 1550	PARKETOLIT 1551	PARKETOLIT 1554	PARKETOLIT 1555	PARKETOLIT E60	PARKETOLIT E61	PARKETOLIT E65	PARKETOLIT E66	PARKETOLIT D3	MEKOL 1560	MEKOL 1570	MEKOL 1580	MITOPUR 1530
<b>SOLID PARQUET ELEMENTS</b>																
• on concrete or on leveller	■	■	●	●	●	●	●	●	●	●	●					
• on wooden floors		■	●	●	●	●	●	●	●	●	●					
• on nonporous surfaces			●	●	●	●	●	●	●	●	●					
• on heated floors			●	●	●	■	■	●	●	●	●					
• on concrete with increasing moisture			■	■	■	■	■	●	●	■	■					
• unstable wood (beech, ash...)			■	■	■	■	●	●	●	●	●					
<b>MOSAIC PARQUET</b>																
• on concrete or on leveller	●	●	●	●	●	●	●	●	●	●	●					
• on wooden floors		●	●	●	●	●	●	●	●	●	●					
• on nonporous surfaces			●	●	●	●	●	●	●	●	●					
• on heated floors	●	■	●	●	●	■	■	●	●	●	●					
• on concrete with increasing moisture			■	■	■	■	■	●	●	■	■					
• unstable wood (beech, ash...)			●	●	●	●	●	●	●	●	●					
<b>SOLID LAMPARQUET</b>			●	●	●	●	●	●	●	■	■					
<b>SOLID BOARDS</b>			●	●	●	●	●	■	■	■	■					
<b>MULTY-LAYER PARQUET</b>			■	■	■	●	●	●	●	●	●	●				
<b>SOLID VERTICAL FINGER PARQUET</b>			●	●	●	●	●	●	●	●	●					
<b>LAMINATED FLOORS</b>								■	■	■	■	●				
<b>PVC</b>													●	●	●	■
<b>TEXTILE COVERINGS</b>													●	●		
<b>CORK (natural, plastic)</b>														●		
<b>RUBBER</b>			■	■	■			■	■	■	■				●	●
<b>LINOLEUM</b>															●	
<b>CERAMIC TILES</b>			■	■	■	■	■	■	■	■	■					■
<b>ARTIFICIAL GRASS</b>			■	■	■	■	■									●
<b>WOODEN STEPS</b>			■	■	■	■	■	■	■	■	■					■

● basic use

■ possible use



MITOL, tovarna lepil, d.o.o., Sežana, Partizanska c. 78, 6210 Sežana, Slovenija  
T: +386 5 73 12 300, F: +386 5 73 12 390, E: [mitol@mitol.si](mailto:mitol@mitol.si), I: [www.mitol.si](http://www.mitol.si)