

PARKETOLIT

ONE COMPONENT POLYURETHANE PRIMER

PR52

ODOUR-FREE - FAST- READY TO USE

Fields of application:

- **Strengthening** of powdery and non-compact surfaces
- **Balancing absorbency** of too porous subfloors
- **Improving the glue adhesion** to surface
- **Renovating the old parquet surface**



On treated surface, all types of parquet can be glued with reactive adhesives Parketolit 1549, 1550, 1551, 1554, 1555, E60, E61, E65, E66 or rubber, PVC and artificial grass can be glued with Mitopur 1530.

Characteristics:

- **Odour-free**
- **Fast hardening** primer allows flooring installation already **45 to 90 minutes** after coating
- **Ready to use**, one component, without diluting
- **Excellent penetration** also into poorly porous subfloor
- **Without material waste**, due to mixing too much product

WE'RE ALWAYS IN BETWEEN



Benefits of using primer:

Before laying floor coverings, surface should be coated with primer in order to:

- Improve hardness of powdery and non-compact subfloor



- Balance absorbency of too porous subfloors



- Improve the glue adhesion to surface



Consumption:

- Highly porous surface: 180 – 250 mL/m²
- Normally porous surface: 120 – 180 mL/m²
- Poorly porous surface: 90 – 120 mL/m²

For more information, please call ++386 **573 12 326** or mail to prodaja@mitol.si.



MITOL, tovarna lepil, d.o.o., Sežana, Partizanska c. 78, 6210 Sežana, Slovenija
T: +386 5 73 12 300, F: +386 5 73 12 390, E: mitol@mitol.si, I: www.mitol.si