

**PARKETOLIT E60**

A one-component STP (silan terminated polyurethane) adhesive, water and solvent-free, for gluing all types of parquet on any kind of subfloor, also on heated floors and on screeds with increased moisture content without using primer. This adhesive is efficient, user-friendly and it is easy to remove excess, it has a neutral odour. Permanently flexible, this adhesive allows natural adaptation of wooden floors to ambient conditions and improves sound isolation of floors.

Yield:  
- dry screed 0,6 – 1,1 kg/m<sup>2</sup>  
- moisture screed till 2,5 kg/m<sup>2</sup>

EAN Code	Packing	Pieces a pallet	Application
383 8958 521141	2x7kg Al vreča	44	notched trowel B3, B11

**PARKETOLIT E65**

A one-component MS water and solvent-free adhesive, for gluing all types of parquet on any kind of subfloor, including heated floors. Joint is permanently flexible. The excess adhesive is easy to remove, meaning it is very suitable for laying prefinished parquet.

EAN Code	Packing	Pieces a pallet	Yield	Application
383 8958 840242	2x7kg Al vreča	44	0,7 – 1,2 kg/m <sup>2</sup>	notched trowel B3, B11



**MITOL, tovarna lepil, d.d., Sežana**  
Partizanska cesta 78, 6210 Sežana, Slovenija  
T : +386 5 73 12 300  
F : +386 5 73 12 390  
E : mitol@mitol.si  
I : www.mitol.si

**MEKOL 1570**

A high-quality solvent-free dispersion adhesive for gluing PVC, textile coverings, plastic and natural cork on levelled cement surfaces or other porous surfaces. Also suitable for laying coverings on walls and on underfloor heating installations. Easy trowel application, high initial grab which allows immediate adhesion, long open time, high final strength and bond elasticity are high performance characteristics of this adhesive.



EAN Code	Packing	Pieces a carton	Pieces a pallet	Yield	Application
383 8958 511333	12 kg		44	0,25 - 0,35 kg/m <sup>2</sup>	notched trowel A1, A2
383 8958 511364	6 kg	2	72		



**MEKOL 1560**

A dispersion solvent-free adhesive for gluing PVC and textile coverings on levelled cement surfaces and other porous surfaces. Also suitable for underfloor heating installations.

EAN Code	Packing	Pieces a pallet	Yield	Application
383 8958 511432	20 kg	24	0,30 – 0,40 kg/m <sup>2</sup>	notched trowel A1, A2

**MEKOL 1580**

A dispersion solvent-free adhesive for gluing rubber, linoleum and PVC coverings on levelled cement surfaces and other porous surfaces. Suitable also for heated floors. High final strength and bond elasticity are high performance characteristics of this adhesive.



EAN Code	Packing	Pieces a pallet	Yield	Application
383 8958 511838	20 kg	24	0,30 – 0,35 kg/m <sup>2</sup>	notched trowel A2

**MITOPUR 1530**

A two-component polyurethane adhesive, highly-volatile-solvents and water free, for gluing rubber, PVC coverings and artificial grass on any kind of subfloor. The joint is flexible, water and temperature resistant, therefore this adhesive is suitable for gluing on screed with increased moisture content and on heated floors. For indoor and outdoor use.

Mixing ratio: **A:B = 6 : 1**



EAN Code	Packing	Pieces a pallet	Yield	Application
383 8958 530136	12 + 2 kg	44	0,8 – 1,2 kg/m <sup>2</sup>	notched trowel B3

**MITOPUR E45**

A one-component polyurethane solvent-free adhesive for the fixing of raised wooden floor tiles. The adhesive is syringed into the bored holes between the cracks of the parquet. The adhesive sets in reaction with water, slightly expands and then spreads and fills the space under the parquet.



EAN Code	Packing	Pieces a carton	Pieces a pallet	Application
383 8958 134587	300 g	12	600	cartridge applicator

**PARKETOLIT PR50**

A one-component polyurethane primer for renovating wooden floors with cracks. The primer should be spread using a trowel on the whole surface. It penetrates between cracks, joins raised parquet with subfloor and fills cracks when sufficiently applied.

EAN Code	Packing	Pieces a carton	Pieces a pallet	Application
383 8958 532543	5L	4	128	trowel

**MEKOL MONT**

A dispersion solvent-free paste assembling adhesive, for fixing raised blocks of parquet, cork, PVC and textile coverings and for quick fixing of battens, styropor and isolation plates etc.



EAN Code	Packing	Pieces a carton	Pieces a pallet	Application
383 8958 512095	300 mL	12	576	cartridge applicator

**PARKETOLIT 1550**

A two-component paste polyurethane adhesive, water and solvent free, for gluing wooden steps on any kind of subfloor. This fast setting adhesive allows the levelling of surfaces and lacquering a day after gluing the steps.

Mixing ratio: **A:B = 6 : 1**

EAN Code	Packing	Pieces a carton	Pieces a pallet	Yield	Application
383 8958 531539	12 + 2 kg		44	1,0-1,5 kg/m <sup>2</sup>	notched trowel B3, B11
383 8958 531546	6 + 1 kg	2	72		

**ADHESIVE FOR LAMINATED FLOORS**



**PARKETOLIT D3**

A dispersion solvent-free adhesive for gluing tongues and grooves in laminated floors and prefinished parquet, where water resistance and a strong joint are required.

EAN Code	Packing	Pieces a carton	Pieces a pallet	Yield	Application
383 8958 510893	500g	12	768	500g /20 m <sup>2</sup>	by bottle

**THE REST OF OUR PRODUCTS**



**SILOPLAST**

A resin for filling wood coverings. When mixed with wood flour, this resin is used as a paste for filling cracks in colour of wooden flooring. It is compatible with all types of coats. The colour of the cracks remains unchanged for years.

EAN Code	Packing	Pieces a carton	Pieces a pallet	Yield	Application
383 8958 540043	5 L	4	96	50-80 mL/m <sup>2</sup>	trowel

**ADHESIVES FOR FLOOR COVERINGS**



## CHOOSE THE RIGHT ADHESIVE

## CHOOSE THE RIGHT ADHESIVE

## PRODUCTS FOR PREPARING SUBFLOORS

## DISPERSION ADHESIVES FOR PARQUET

## TWO-COMPONENT REACTIVE ADHESIVES FOR PARQUET

	PARKETOLIT 1513	PARKETOLIT 1514	PARKETOLIT 1549	PARKETOLIT 1550	PARKETOLIT 1554	PARKETOLIT 1555	PARKETOLIT E60	PARKETOLIT E65	PARKETOLIT D3	MEKOL 1560	MEKOL 1570	MEKOL 1580	MITOPUR 1530	MITOPUR E45	MEKOL MONT
<b>WOODEN BLOCKS</b>															
● on concrete or on leveller	●	●	●	●	●	●	●	●							
● on wooden floors		●	●	●	●	●	●	●							
● on nonporous surfaces			●	●	●	●	●	●							
● on heated floors			●	●	■	■	●	●							
● on concrete with increased moisture			■	■	■	■	●	■							
● unstable wood (beech, ash...)			■	■	■	●	●	●							
<b>MOSAIC FLOORS</b>															
● on concrete or on leveller	●	●	●	●	●	●	●	●							
● on wooden floors		●	●	●	●	●	●	●							
● on nonporous surfaces			●	●	●	●	●	●							
● on heated floors	●	■	●	●	■	■	●	●							
● on concrete with increased moisture			■	■	■	■	●	■							
● unstable wood (beech, ash...)	■	■	●	●	●	●	●	●							
LAM PARQUET			●	●	●	●	●	●							
SOLID STRIPS			●	●	●	●	●	●							
PREFINISHED PARQUET			■	■	●	●	●	●	●						
LAMINATED FLOORS									■	■	●				
PVC										●	●	●	●		■
TEXTILE COVERINGS										●	●				■
CORK (natural, plastic)										●					■
RUBBER			■	■			■	■				●	●		
LINOLEUM												●			
CERAMIC TILES			■	■	■	■	■	■					■		■
ARTIFICIAL GRASS			■	■	■	■	■	■					●		
WOODEN STEPS			●	●	■	■	■	■					■		■
BATTENS															●
FLOOR REPAIRING														●	●

● BASIC USE

■ POSSIBLE USE

Before laying floor coverings, the cement surface should be coated with primer in order to:

- improve hardness of the subfloor
- balance absorbency of too porous subfloors
- improve the adhesion of the glue to surface
- allow the laying of parquet on cement screeds with increased moisture content
- halve the time needed for laying wooden floors



### PARKETOLIT PR15

A dispersion primer, which strengthens and binds absorbent and powdery cement substructures. On treated surfaces parquet, cork, PVC, textile coverings, rubber or linoleum can be glued with all types of adhesives or a leveller should be laid.

EAN Code	Packing	Pieces a carton	Pieces a pallet	Yield	Application
383 8958 513542	5L	4	128	50-150 mL/m <sup>2</sup>	roller

### PARKETOLIT PR50

A one-component polyurethane primer, which restores and strengthens porous, powdery and humid cement substructures. Sets in reaction with water. On treated surfaces, all types of parquet can be glued with reactive adhesives PARKETOLIT 1549, 1550, 1554, 1555, E60, E65 or rubber, PVC coverings and artificial grass can be glued with MITOPUR 1530.

Yield:  
 - surface strengthening 100-300 mL/m<sup>2</sup>  
 - humid surfaces 400-500 mL/m<sup>2</sup>



EAN Code	Packing	Pieces a carton	Pieces a pallet	Application
383 8958 532543	5L	4	128	roller

### MITOSOL S50

A thinner for diluting the PARKETOLIT PR50 primer and for removing adhesive residues after gluing with reactive adhesives.

EAN Code	Packing	Pieces a carton	Pieces a pallet
383 8958 532949	5L	4	128

### PARKETOLIT 1513

A coloured dispersion paste and solvent-free adhesive, with low water content for laying wooden blocks and mosaic floors on concrete. Allows gluing on rough and heated floors.



EAN Code	Packing	Pieces a carton	Pieces a pallet	Yield	Application
383 8958 510732	25 kg	2	24	0,7-1,0 kg/m <sup>2</sup>	notched trowel B3, B11
383 8958 510763	7 kg		72		

### PARKETOLIT 1514

A dispersion solvent-free adhesive, with low water content for laying wooden blocks and mosaic floors on concrete and other porous surfaces. Among dispersion adhesives allows the quickest lacquering after laying parquet.



EAN Code	Packing	Pieces a carton	Pieces a pallet	Yield	Application
383 8958 510831	25 kg	2	24	0,6-1,0 kg/m <sup>2</sup>	notched trowel B2, B3
383 8958 510862	7 kg		72		

### PARKETOLIT 1550

A two-component water and solvent-free paste polyurethane adhesive, for gluing all types of parquet on any kind of subfloor. The joint is water and heat resistant, therefore the adhesive is suitable for gluing on screed with increased moisture content and on heated floors. For indoor and outdoor use. This fast setting adhesive allows levelling and lacquering a day after laying parquet.

Mixing ratio: **A:B = 6:1**



EAN Code	Packing	Pieces a carton	Pieces a pallet	Yield	Application
383 8958 531539	12+2 kg	2	44	1,0-1,5 kg/m <sup>2</sup>	notched trowel B3, B11
383 8958 531546	6+1 kg		72		

### PARKETOLIT 1549

A two-component polyurethane adhesive, water and highly-volatile-solvents free, for gluing all types of parquet on any kind of subfloor. Adhesive is suitable for gluing on heated floors and screed with increased moisture content. For indoor use. Lacquering of parquet is possible a day after laying parquet.

Mixing ratio:  
**A:B = 12,85 : 1,15**



EAN Code	Packing	Pieces a carton	Pieces a pallet	Yield	Application
383 8958 531737	2,85+1,15 kg	2	44	1,0-1,5 kg/m <sup>2</sup>	notched trowel B3, B11
383 8958 531744	6,43+0,57 kg		72		

### PARKETOLIT 1555

A two-component epoxy-polyurethane adhesive, water and highly-volatile-solvents free, for gluing all types of parquet on any kind of subfloor. The excess adhesive is easy to remove, meaning it is very suitable for laying prefinished parquet. This slow-setting adhesive allows dimensional balancing of unstable kinds of parquet, for example beech, ash.

Mixing ratio: **A:B = 13 : 1**



EAN Code	Packing	Pieces a pallet	Yield	Application
383 8958 532031	13+1 kg	44	1,0-1,5 kg/m <sup>2</sup>	notched trowel B3, B11

### PARKETOLIT 1554

A two-component water free epoxy-polyurethane adhesive for gluing all types of parquet on any kind of subfloor. Suitable for laying parquet on heated floors and on screed with increased moisture content. The excess adhesive is easy to remove, meaning it is very suitable for laying prefinished parquet. Lacquering of parquet is possible a day after laying parquet.



Mixing ratio:  
**A:B = 14 : 1**

EAN Code	Packing	Pieces a pallet	Yield	Application
383 8958 840259	14+1 kg	44	1,0-1,5 kg/m <sup>2</sup>	notched trowel B3, B11